

DIR911t

Advanced Technology Instant Recall and Logging System



Eventide—the company that invented the digital voice audio logger—turned its attention to instant recall devices. We found that most units had one glaring omission. When the incoming telephone call or radio transmission is difficult to understand, the operator can play it again, but can't hear it more clearly.

INTELLICLEAR VARIABLE SPEED CONTROL

Drawing on our expertise in professional recording and broadcasting, we changed that with the IntelliClear™ variable speed control. This feature lets the operator slow down the play back (or speed it up) without changing the pitch or degrading the sound quality. This breakthrough—made possible by advanced DSP (digital signal processing) circuitry—is nothing like the “slow” speed button offered by other units, which often makes audio harder to understand. Slowing down the replay with IntelliClear actually increases intelligibility. Operators can frequently understand speech which had been hopelessly garbled.

To make IntelliClear even more useful, we rethought the conventional rewind/fast forward controls found on other recall devices. They're useful on a tape recorder, but on a recall unit conventional rewind/fast forward buttons overshoot the desired segment within a message which results in the operator having to “hunt and peck” awkwardly until the right segment is found. The DIR911t's rewind and fast forward work differently. The single control wheel located beside the recall button provides precise jogging backward and forward by simply turning the wheel to the left or right. It's fast and easy-to-use—ideal for high-pressure public safety operations.

WINDOWS PC CONTROL

The MediaWorks™ client provides password-protected remote access to a DIR911t call record database, and the MediaAgent™ client provides instant recall. Multiple DIR911t instant recall recorders can be seamlessly integrated into your existing network infrastructure. MediaWorks and MediaAgent are self-installing and self-contained, scalable clients which require minimal system resources, yet provide access to the DIR911t from an unlimited number of standard Windows PC workstations with up to four simultaneous user connections.

LARGE DISPLAY

The DIR911t's back-lit 4 line by 40 character LCD screen is much larger than those on other recall units, and shows a wider range of information. Telephone numbers can be captured from DTMF, Caller ID, or ALI data stream, and will appear on the display. All message information such as time/date, message number, message lengths, etc. are clearly shown. For operating ease, the bottom line of the LCD dynamically labels four “soft key” buttons with the proper designations for each operating mode.

FULLY FEATURED

The DIR911t has a full two hours to 61 hours of digital RAM storage in either two-, four-, six-, or eight-channel configurations. 14,393 hours of storage is available with dual RAID-1 100GB hard disks. Password security protects the system set-up parameters from being accidentally changed or erased. The DIR911t can be either a desktop or a 5.25" x 19" single or dual rack mount. The choice in instant recall units for public safety applications is clear. The DIR911t with IntelliClear variable speed control is in a class by itself!

CHOOSE EVENTIDE

For over 36 years, Eventide has built a reputation for technological innovation and time-tested reliability. Thousands of customers world-wide have come to depend on Eventide for mission-critical operations. For more information about the DIR911t, call Eventide at 201-641-1200 or visit WWW.EVENTIDE.COM

Specifications subject to change without notice or obligation.



MediaWorks™ Interface

FEATURES

STANDALONE INSTANT RECALL
RECORDER FEATURING LOCAL
CONTROL

INTELLICLEAR™ AUTOMATICALLY
ENHANCES INTELLIGIBILITY WITH
DSP PITCH CORRECTION

AVAILABLE IN 2, 4, 6, OR 8 CHANNELS

2 TO 14,000 CHANNEL HOURS OF
RECORDING

COMPACT DESIGN - STANDALONE OR
RACK MOUNT

NONPROPRIETARY RECORDING
APPLIANCE FEATURING EMBEDDED
LINUX O/S FOR INCREASED RELIABIL-
ITY AND A MORE COST-EFFECTIVE
SYSTEM

REMOTE CONTROL VIA WINDOWS PC
WORKSTATIONS WITH EVENTIDE
MEDIAWORKS OR MEDIAAGENT
CLIENTS

EASY-TO-USE JOG FORWARD AND
BACKWARD, AND SPEED CONTROL
KNOB

DIAL-IN REMOTE DIAGNOSTICS

input jacks, serial
data I/O ports, USB connectors,
Ethernet connector, locking 12V power
connector, enable/disable battery

TIMECODE

Resolution – 1 second, accuracy – 2
seconds per day
external sync – RS232 format 0, 1, or 2;
NTP server or GPS receiver

NETWORK

Ethernet 10/100Mbps, TCP/IP protocol,
MediaWorks and MediaAgent
Windows-based clients, up to 4
simultaneous accesses, with desktop
instant recall

ELECTRICAL

Frequency response: 200 to 3400 Hz
Signal-to-noise ratio: greater than
-50dB
Distortion: less than 3%
Audio input level: -35dB to +5dB
with AGC
Input impedance: 10kOhm balanced

WEIGHT

3 lbs. excluding rack ears and power
supply

DIMENSIONS

Desktop – 5.5"H x 8.25"W x 6.5"D
Single rack mount 5.25"H x 19"W x
6.5"D

POWER

12VDC/18 watts, external power
supply – 115V/230V AC power
supply Included

Specifications subject to change
without notice or obligation.

Eventide is a registered trademark;
MediaWorks, MediaAgent, and MediaCoach
are trademarks of
Eventide Inc.

All other trademarks are the property of their
respective owners.

©2007 Eventide Inc.

AUDIO COMPRESSION RATES IN CHANNEL HOURS @ 8kHz SAMPLE RATE (16kHz Rate is Selectable)

Storage	PCM-128kbps	A-Law-64kbps	Mu-Law-64kbps	G726-32kbps	GSM 13.3kbps
128MB	2 hours	4 hours	4 hours	8 hours	20 hours
384MB	6 hours	12 hours	12 hours	25 hours	61 hours
100GB	1,484 hours	2,968 hours	2,968 hours	5,937 hours	14,393 hours

Communications Division

One Alsan Way, Little Ferry, NJ 07643, USA
www.eventide.com loggers@eventide.com
tel: 201.641.1200 fax: 201.641.1640